PLAN

7"
TYP.

2" - TYP.

7'-6"
TYP.

MOUNTING PLATE

CONCRETE CURB

7" 2" 5"
TYP. TYP.

5"
TYP.

BLUNTING

(2) 3/4" X 2" FRAME POSTS

15'-4 3/4" - TYP.

10"

10"

TO FINISHED GRADE

6'-0"

1'

1'

EQ.

EQ.

1'

1'

1/2"

5"

4"

1 3/4" X 1/2" ANGLE RAILS
WELDED TO POSTS.

FRAME POST (TYP).
3/4" X 2"

6" x 5" HINGE (TYP).
STANLEY # F179
OR APPROVED EQUAL.

TOP AND BOTTOM RAILS
1 3/4" X 1/2"

1 3/4" X 1 3/4" X 1/4" X 1 5/8"
LONG ANGLES SHALL BE FULLY
WELDED TO RAILS & POSTS
ON DOUBLE & SINGLE GATES.

BOLT LIFT
BOLT LATCH

5/8" x 5/8" PICKETS SET
DIAGONALLY & FULLY
WELDED TO TOP OF RAILS.

DOUBLE POST. TYPICAL FOR
DOUBLE GATE END-POST.
EACH POST IS 2" SQ.

2"

2"

SEE PLANS FOR FENCE
TYPE AND HEIGHT

TOP OF CURB FLUSH
WITH FINISHED GRADE

2'

GATESTOP

MOUNTING PLATE

DRY, FIRM, COMPACTED SUBGRADE.

ELEVATION / SECTION

6'-0" STEEL BAR DOUBLE GATE IN FLUSH CURB FOR COMPACTOR AREA

Not to Scale