



PRECOMPRESSED SEALANT "COMPRIBAND" AS MANUFACTURED BY PROGRESS UNLIMITED, INC. OF NY. SEALANT TO BE COMPRESSED DOWN TO 15% OF ORIGINAL VOLUME WHEN INSTALLED.

BOND BREAKER TAPE BETWEEN

TYPE 1 SEALANT AT ALL EXPOSED SURFACES

DETAIL "A"

3/4" CHAMFER AT EXPOSED FACES

EXPANSION CAP

3/4" EXPANSION JOINT

1'-0"

2"

3/4" DIA BY 2'-0" LONG SMOOTH DOWELS @ 12" OC

SEE DETAIL "A"

NOTES:

1. EXPANSION JOINT SPACING NOT TO EXCEED 40 FT.
2. TYPE 1 SEALANT TO BE SELECTED FOR MIN. 50% JOINT MOVEMENT CAPACITY.
3. COORDINATE EXPANSION JOINT AND FENCES SLEEVE LOCATIONS WITH ARCHITECTURAL DRAWINGS.
4. FENCE POST SHOULD BE LOCATED A MINIMUM OF 2'-3' FROM EXPANSION JOINT.
5. FOR REINFORCEMENT AND THICKNESS, SEE WALL SECTIONS.
6. SEE DETAIL FOR REBAR SCHEDULE (WAL-11)



New York City Housing Authority
 Capital Projects Division
 Design Department
 90 Church Street, 10th Floor
 New York, NY 10007

Title:

**EXPANSION JOINT
 FOR CONCRETE
 RETAINING WALL**

Contract Name:

GROUNDS REQUIREMENT

Contract No.

GD XXXXXXX

Drawn by:

G. SOUKAS

Checked by:

K. MARSHAL

Scale:

Not to Scale

Date:

January 2017

Drawing No.

WAL- 04