


- NOTES-**
1. NUMBER OF STEPS VARIES. SEE PLAN.
 2. TOP STEP SHALL MEET PAVEMENT FLUSH.
 3. CONCRETE STEPS MUST BE POURED ON A WELL COMPACTED SUBGRADE.
 4. SEE PLANS FOR SPOT ELEVATIONS OF STEPS AND WALLS.
 5. HEIGHTS OF RISERS SHALL BE EQUAL. 4" MINIMUM, 7" MAXIMUM.
 6. EXPANSION JOINTS SHALL BE PLACED IN WALLS EVERY 25 FEET.
 7. FOR FENCE/HANDRAIL DETAIL SEE (SBF-05).
 8. SEE DETAIL FOR REBAR SCHEDULE (WAL-11).

STEPS Section

CHEEKWALL Section

 <p>New York City Housing Authority Capital Projects Division Design Department 90 Church Street, 10th Floor New York, NY 10007</p>	<p>Title: Concrete Steps With Cheekwalls And Spread Footing- PipeRail or Fence in Steps</p>	
<p>Contract Name: GROUNDS REQUIREMENT</p>	<p>Contract No.: GD XXXXXX Scale: Not to Scale Scale: Not to Scale Drawn by: G. SOUKAS Checked by: K. MARSHAL Date: January 2017</p>	<p>Drawing No.: WAL- 09</p>