

SECTION 10 14 00 SIGNAGE

PART 1 GENERAL

1.01 REFERENCE STANDARDS

- A. 36 CFR 1191 - Americans with Disabilities Act (ADA) Accessibility Guidelines for Buildings and Facilities; Architectural Barriers Act (ABA) Accessibility Guidelines; current edition.
- B. ADA Standards - 2010 ADA Standards for Accessible Design; 2010.
- C. ICC A117.1 - Accessible and Usable Buildings and Facilities; 2017.

1.02 SECTION INCLUDES

- A. Exterior signs.

1.03 REFERENCE STANDARDS

- A. 36 CFR 1191 - Americans with Disabilities Act (ADA) Accessibility Guidelines for Buildings and Facilities; Landscape Architectural Barriers Act (ABA) Accessibility Guidelines; current edition.
- B. ADA Standards - Americans with Disabilities Act (ADA) Standards for Accessible Design; 2010.
- C. ICC A117.1 - Accessible and Usable Buildings and Facilities; International Code Council; 2009 (ANSI).

1.04 SUBMITTALS

- A. See Section 01 33 00 – Submittal Procedures, for submittal procedures.
- B. Product Data: Manufacturer's printed product literature for each type of sign, indicating sign styles, font, foreground and background colors, locations, overall dimensions of each sign.
- C. Signage Schedule: Provide information sufficient to completely define each sign for fabrication, including room number, room name, other text to be applied, sign and letter sizes, fonts, and colors.
 - 1. When content of signs is indicated to be determined later, request such information from NYCHA through Landscape Architect at least 2 months prior to start of fabrication; upon request, submit preliminary schedule.
 - 2. Submit for approval by NYCHA through Landscape Architect prior to fabrication.
- D. Samples: Submit two samples of each type of sign, of size similar to that required for project, illustrating sign style, font, and method of attachment.
- E. Selection Samples: Where colors are not specified, submit two sets of color selection charts or chips.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Package signs as required to prevent damage before installation.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Flat Signs:
 - 1. Best Sign Systems, Inc; Product: Accessible Parking Sign "SS56", 12" x 18", Steel. www.bestsigns.com.
 - 2. Leeds Landscape Architectural Letters of Alabama, Inc., phone 205.699.5271 Custom 12" x 18" sign for play areas, black letter on white background. See Detail for text.
 - 3. or Equal

2.02 SIGNAGE APPLICATIONS

- A. Accessibility Compliance: Signs are required to comply with ADA Standards and ICC A117.1 and applicable building codes, unless otherwise indicated; in the event of conflicting requirements, comply with the most comprehensive and specific requirements. Signs may be mounted on posts (including footings) or on adjacent fencing

2.03 SIGN TYPES

- A. Accessible Signage Color and Font: Unless otherwise indicated:
 - 1. Character Font: Helvetica.
 - 2. Character Case: Upper case only.
 - 3. Background Color: White
 - 4. Character Color: Blue
 - 5. Symbol: as indicated

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify that substrate surfaces are ready to receive work.

3.02 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Install neatly, with horizontal edges level.
- C. Locate signs where indicated:
 - 1. If no location is indicated obtain NYCHA's instructions.
- D. Protect from damage until Substantial Completion; repair or replace damage items.

END OF SECTION 10 14 00